


Building Envelope Airtightness Quantification

Challenges applying sectional, sampling, or wall assembly testing methods

Stephen Wong, P.Eng.

Principal, Building Science Engineer



Understanding the Validity and Repeatability of Airtightness Results

- Is this the right testing approach for this project (Specs, SOR, Memos)?
- How are we applying and interpreting these tests results?
- Understanding can help avoid:

- Liability of misrepresentations (assemblies represents BE)
- Risk of misinterpretation (false passes/fails)
- Costly re-testing
- Losing faith on test approach

- Who needs to understand?

- Developers, owners
- Designers, architects, engineers, consultants
- Builders
- Authorities Having Jurisdictions, Building/Code Officials
- Commissioning Agents
- Testers



The Standards: *Building Envelope Airtightness*



ASTM E-779



US Army Corps of Engineers
(USACE)



ASTM E-3158


Whole Building

The high-rise is treated as one zone

Preparation is simpler

Distribute testing equipment

No pressure neutralization required



Building Envelope Airtightness testing

Whole Building Envelope

- Fans pressurize/depressurize the entire building (at multiple pressure setpoints)
- Measure pressures
- Calculate airflows
- Calculate air leakage rates based on building enclosure area (or volume)




photo: Efficiency Matrix

Wall Assembly Airtightness?

Can we make a direct interpretation on *Envelope* Airtightness based on measuring an *Assembly* Airtightness?



ASTM E-783

Intended for **Windows and Doors**

The Standards: *Wall Assemblies' Airtightness*



ASTM E-283

Fenestrations
(Laboratory)



ASTM E-783

Fenestrations
(Field)



ASTM E-2178

Materials

Wall Assembly Airtightness?


Can we make a direct interpretation on *Envelope* Airtightness based on measuring an *Assembly* Airtightness?



ASTM E-779

Intended for Whole **Building Envelope** Airtightness

e.g. **0.4 CFM/ft² @ 75 Pa**



ASTM E-783


Intended for **Windows and Doors**

e.g. **0.1 CFM ft² @ 300 Pa** (NAFS AW performance)

Compartments

Sectional method (vs Whole Building)


Multiple mobilizations (vs Single mobilization)



Compartments

Sampling method

Multiple mobilizations (vs Single mobilization)



Partial Building Airtightness?

“Compartmentalized” test

– How is this compartment airtightness being quantified and evaluated?




photo: Efficiency Matrix




Wall

Airtightness Test

Partial Building Airtightness?

“Compartmentalized” test

– How is this compartment airtightness being quantified and evaluated?




Single Floor (alone)

Airtightness Test

Pressure Neutralization



Theory:

Leakage is only measured across areas with pressure differential – True or False?




Partial Building Airtightness?

Reality Vs Theoretical/Expectation



Floor-by-Floor
Approach





Unit-to-Unit
Approach


Partial Building Airtightness?

Theory – Pressure Neutralization Testing Approach

– Are testers' non-standardized approaches becoming more innovative? Or becoming misleading?



Floor-by-Floor
Approach



Unit-to-Unit
Approach

photos: Retrotec

Partial Building Airtightness?

Data uncertainties and inaccuracies largely unrecognized - ASHRAE research paper (RP-4275)

4275 (RP-935)

Protocol for Field Testing of Tall Buildings to Determine Envelope Air Leakage Rate

William P. Bahnfleth, Ph.D., P.E.
Member ASHRAE

Grenville K. Yuill, Ph.D., P.E.
Fellow ASHRAE

Brian W. Lee
Student Member ASHRAE

ABSTRACT

The objective of this project was to develop a relatively simple, accurate method for testing the overall envelope leakage rate of tall buildings. Two fan pressurization test techniques, the floor-by-floor blower door method and the air-handler method, were developed and tested on two buildings. Criteria for conducting accurate tests were developed, including limitations on outdoor air temperature and wind speed. The floor-by-floor blower door method permits isolation and measurement of the leakage flow rate of a single floor, but it is difficult and time-consuming to apply. The air-handler method uses building air distribution fans for pressurization. It is most easily applied on a system-by-system level rather than floor-by-floor. Fan airflow techniques including orifice plate, pitot traverse, and tracer gas dilution were considered. The tracer gas method was found to be relatively easy to apply and highly accurate. Fan airflow rate measurement uncertainty by tracer gas was estimated to be 5.4% to 8.8% for the cases considered, assuming a 5% uncertainty in interzonal leakage.

INTRODUCTION

Building envelope tightness is of importance to owners, operators, and tenants of tall buildings for operational, indoor environmental quality and financial reasons. Airflows through envelope leakage paths caused by pressure differential due to stack effect and wind have several undesirable effects. Uncontrolled entry of unconditioned outdoor air into occupied spaces may adversely affect comfort. Movement of air within a building as a result of envelope leakage may transfer contaminated air. Leakage also adds to air-conditioning peak loads and total energy consumption. The movement of air

through the envelope can cause serious moisture problems if air is cooled to its dew point while within an exterior wall. Stack effect pressure differential across building shafts can generate objectionable noise that is particularly evident at stairwell and elevator doors. In view of the negative consequences of envelope leakage, construction methods to limit leakage and testing procedures to verify their efficacy should be a part of building design and commissioning.

Measurement of the envelope leakage of houses and other small buildings through pressurization and depressurization testing is a common procedure (Shaw et al. 1990). The typical test method utilizes a temporarily installed fan to pressurize or depressurize the building to a series of desired indoor-outdoor pressure differentials. The airflow rate into or out of the building is measured at steady state for each differential. Data from these tests are used to establish a correlation between airflow and pressure differential. In principle, this approach is also applicable to tall buildings. However, stack and wind effects and the large flow rates required for standard leakage tests make the application of these techniques to tall buildings less than straightforward.

The objective of ASHRAE Research Project 935 (Bahnfleth et al. 1998) was to develop a method to evaluate the airtightness of the envelope of tall buildings that represents the best compromise between simplicity and accuracy. Two leakage test procedures were developed for tall buildings by extension of established pressurization test procedures. Criteria for accurate application of these methods to tall buildings were developed. The procedures were tested in two different buildings and evaluated according to criteria including the value of the information acquired, ease of use, and degree of disruption of building operations.

William P. Bahnfleth is an assistant professor in the Department of Architectural Engineering, Pennsylvania State University, University Park, Pa. Grenville K. Yuill is director of Architectural Engineering at the University of Nebraska, Omaha, Neb. Brian W. Lee is a health facilities officer at the U.S. Air Force Health Facilities Division, Atlanta, Ga.

RESULTS

Floor-by-Floor Blower Door Method


Testing was conducted first at the university library site, beginning with the floor-by-floor blower door method. Numerous attempts were made to execute this procedure, but adequately sealing a single floor to isolate it from its neighbors was found to be impossible. Elevators, doors, ducts, and other apparent leakage paths were carefully and completely sealed, yet a large amount of additional, inaccessible floor-to-floor leakage remained. This was evident because, with the test floor sealed and adjacent floors pressurized by additional blower doors, high pressures were recorded on the test floor when the blower door fan was off. The inability to adequately seal the test floor is perhaps more significant in view of the fact that a crew of four workers spent nearly three hours in the effort on each occasion that the procedure was tested. Extrapolating this level of effort very roughly to the larger office building, one obtains an estimate on the order of 500-1,000 person hours simply to seal interfloor leakage paths.

Further efforts to find hidden leaks did not substantially reduce interzonal leakage. Numerous holes and cracks that could not be reached and sealed were found in return risers and elevator shafts. Further, the return air shaft was found to be constructed of 16 in. concrete masonry unit (CMU) blocks that offer only a small resistance to airflow. Sealing this return shaft leakage was not feasible. It was concluded on the basis of these discouraging experiences that the floor-by-floor blower door test method is impractical for general use and it was not tested further.

Partial Building Airtightness?

“Compartmentalized” test

– How is this compartment airtightness being quantified and evaluated?



Single Floor (pressure-neutralized)

Airtightness Test

Partial Building Airtightness?

Empirical data - High Degrees of Data uncertainties and inaccuracies can be largely unrecognized

Test #1	Date	Levels	Primary System	Target	Result	Result
1	9/29/2023	20-21	Window wall	0.25 cfm/ft2	0.35 cfm/ft2	Fail
2	10/6/2023	20-27	Window wall	0.25 cfm/ft2	0.35 cfm/ft2	Fail
3	10/13/2023	20-27	Window wall	0.25 cfm/ft2	0.147 cfm/ft2	Pass

Floor Re-tests

(varying interior compartmentalization and preparation)

Mobilization	MOBILIZATION 1 (3/25/2022)		MOBILIZATION 2 (4/08/2022)		MOBILIZATION 3 (4/15/2022)	
Test	1	2	1	2	1	2
Direction	Pressurization	Depressurization	Pressurization	Depressurization	Pressurization	Depressurization
Start Time	1:43:15 PM	1:56:37 PM	12:05:27 PM	3:13:59 PM	1:28:42 PM	1:48:18 PM
Enclosure Area	8381	8381	8381	8381	8549	8549
Neutralization Floors	9 & 11	9 & 11	18 & 21	18 & 21	28 & 31	28 & 31
Tested Floors	10 & 11	10 & 11	19 & 20	19 & 20	29 & 30	29 & 30
Flow per envelope area at 75 Pa	0.331	0.167	0.292	0.111	0.182	0.096
Combined	0.249		0.202		0.139	
Correlation	0.999	0.999	0.989	0.991	0.996	0.994
Slope	0.805	0.586	0.792	0.600	0.725	0.668
Notes	No changes in floor-plate of test levels		No changes in floor-plate of test levels		No changes in floor-plate of test levels	

Various Floors, but same Floor Plate

(pressure –neutralizing repeatability issues)

Partial Building Airtightness?

What do standards say about testing a portion of a building?

Larger Buildings

Buildings requiring flow in excess of 200,000 cfm at 75 Pa have been successfully tested using standard techniques. Some larger buildings may require special test techniques not covered in this document primarily because of limitations in *test fans*. One option is to separate the building into multiple temporary test zones using boundary pressure neutralization techniques. A second option is to erect temporary walls to create multiple test zones. A third option may be to use the building HVAC system to establish test pressures. These three special techniques will require a higher level of experience and engineering to establish useful results. It is up to the specifier to establish conformance criteria and test procedures for these unique buildings with the help of the testing agency. The Canadian General

The pressure exponent, n , will also provide some insight as to the validity of the test and relative tightness of the *building envelope*. Exponent values less than 0.50 or greater than 1.0 in theory indicate a bad test, but in practice, tests outside the range of 0.45 to 0.80 would generally indicate an inaccurate

USACE Air Leakage Test Protocol for Building Envelopes – Version 3: 2012-05-11

USACE

Keywords: “**require higher level of experience and engineering**” which on the surface appears to suggest it could be possible, until you truly understand the requirements and caveats:

separate test envelopes and tested separately. While testing isolated subsections, monitoring must be conducted for any extraneous/flanking air movement between the different zones.


ASTM E-3158

- Keywords: “**monitor**” and avoid “**any extraneous air movement between different zones**”, which ASHRAE research paper (RP-4275) claims “isolating [floor] from its neighbor was found to be impossible” (attached)

Partial Building Airtightness?

Data uncertainties and inaccuracies largely unrecognized – Empirical data


Flow vs Induced Pressure (Pressurize Set)



Expectation

$n = 0.45$ to 0.8

Flow vs Induced Pressure (Pressurize Set)




Reality

$n = -0.11$


Partial Building Airtightness?

“Compartmentalized” test

– How is this compartment airtightness being quantified and evaluated?



Floors (alone)
Airtightness Test



Floors (pressure-neutralized)
Airtightness Test

Partial Building Airtightness Test Results

- Simply checking off a box – just get a number?
 - Are the lines becoming blurred on what's an acceptable standard test approach?
 - Is the number accurate?
 - Is the number misleading?
 - How is this number applied or evaluated?
 - Could the results be misrepresenting the whole building?
 - Could owners, developers, builders be misled on BE issues or lack thereof?
 - Are AHJs, Building/Code officials aware of quantification issues?
 - What are the risks and liabilities on design and construction?
 - Does re-testing have to be performed?
- Better understanding and discussions with stakeholders on its limitations
 - Understand the *data* to determine its *validity*
 - Understand the *results* to determine its *accuracy/repeatability*




The background of the slide is a dark blue, textured pattern consisting of many 3D cubes or hexagonal prisms arranged in a staggered, overlapping grid. The lighting creates a sense of depth and three-dimensionality.

Thank You

Get in touch



Stephen Wong, P.Eng.
swong@morrisonhershfield.com



National Institute of Building Sciences
1090 Vermont Avenue NW, Suite 700
Washington, DC 20005
(202) 289-7800
nibs@nibs.org

